

Instructions for Flashlight

High Powered Tactical Flashlight

Built for Police, Military, Security Forces, Emergency Services, and other Professionals

Introduction:

These flashlights produce an ultra-bright beam by using State of the Art LED bulb technology. They are designed for easy, one-hand operation and are equipped with a multi-mode switch for various light beam intensities and strobe functions. The rugged bodies are manufactured by high precision machines using aircraft-grade aluminum alloy for long lasting durability. The flashlights, including the tail switches are designed to be water-resistant in normal use.

These instructions apply to the T6 and Q5 flashlights (Part of the EcoGear FX Flashlight Kit, Part Number EGFX-T6KIT and EGFX-Q5KIT)

Warning (Read carefully before using this flashlight!)

Lithium batteries can explode or cause burns if shorted, overheated, disassembled, recharged or exposed to fire or high temperatures (above 212° F). This flashlight is an ultra-high power flashlight. If the flashlight is turned on while in a container or in clothing, the flashlight can overheat, damage the flashlight, and cause surrounding material to ignite. Remove batteries from the flashlight and recharge the batteries when the flashlight is getting dim or unusable. Replace with new batteries when the batteries have failed to recharge normally. Never mix fresh batteries with used lithium batteries or mix different brands of batteries. Personal injury and/or property damage can result if these instructions are not followed. Please handle with care.

Battery Charging:

The rechargeable battery needs to be fully charged before use. Battery charging time typically takes 3-4 hours for a 3000mAh capacity battery. The battery charger light will indicate when the battery is fully charged. Always charge the batteries on a fire-proof surface. Never leave charging batteries unattended.

To Insert Battery:

1. Remove the tail cap by turning counterclockwise until it detaches from the rear of the flashlight body.
2. Insert a single 18650 3.7 volt lithium battery. Insert battery "+" end toward the head.
3. Reinstall the tail switch on the rear of the flashlight by turning clockwise.

Operation:

Press the tail switch to turn the light is on. Be sure that the lamp assembly and the head assembly are fully tightened on the front end of the body. Press the tail switch again to turn off. To activate the different light modes press the tail switch twice repeatedly (to advance to the next mode repeat this step).

Storage:

Remove battery from the flashlight if it will not be used for an extended period of time.

Replacement of Lamp Assembly:

1. Remove the battery from the flashlight.
2. Unscrew the smooth front section (with clear lens) from around the reflector on the head assembly.
3. Lift out the bulb and reflector assembly.
4. Place the new bulb securely into the light. Screw the front section with the lens back into place and tighten securely.

General Care and Maintenance:

1. Clean the O-rings and O-grooves with a soft clean cloth regularly to ensure that the seals are free of dirt.
2. Lubricate the O-rings by applying a light coat of clear silicon grease regularly.
3. Remove the tail switch and clean the threads on the body and inside of the tail switch with a soft clean cloth.

Instructions for T6 and Q5 High Powered Tactical Flashlights



7108 Katella Avenue
Unit 418
Stanton, CA 90680
714-893-5020